



DT-588

- Solid rib design combined with multiple sipes
- Four wide circumferential grooves
- Reinforced shoulder design
- Excellent heat dissipation and improved wear with lower rolling resistance
- Compound provides resistance to abrasion



Regional Application



Enhanced Mileage



Optimized Handling



Multiple Retreads

SIZE	PLY	LOAD RANGE	LOAD/SPEED INDEX	MAX. LOAD		MAX. PRESSURE PSI	MEASURE RIM WIDTH (inch)	OVERALL DIAMETER (inch)	SECTION WIDTH (inch)	TREAD WIDTH (32nd)	TREAD DEPTH (32nd)
				SINGLE	DUAL						
11R22.5	16	H	146/143L	6610	6005	120	8.25	41.4	11.0	8.35	18.9
11R24.5	16	H	149/146L	7160	6610	120	8.25	43.4	11.0	8.35	18.9
225/70R19.5	14	G	128/126L	3970	3750	110	6.75	31.8	9.3	6.69	16.4
245/70R19.5	16	H	135/133L	4805	4540	120	7.50	33.0	10.1	7.32	16.4
255/70R22.5	16	H	140/137L	5510	5070	120	7.50	36.4	10.4	7.87	16.4
295/75R22.5	16	H	146/143L	6610	6005	120	9.00	39.8	11.6	8.50	19.5

RECOMMENDED WHEEL POSITION

